## **SAFETY DATA SHEET**

100% RTV SILICONE SEALANT

**SECTION 1: PRODUCT AND COMPANY IDENTIFICATION** 

PRODUCT NAME: AC1230 SERIES 100% INDUSTRIAL RTV SILICONE SEALANT

DISTRIBUTOR: AMERICAN CHEMICAL, INC ADDRESS: 2201 NORTH 2<sup>ND</sup> STREET MINNEAPOLIS, MN 55411

EMERGENCY PHONE: 800-245-8348
OTHER CALLS: 612-522-4707
FAX PHONE: 612-529-8645

**CHEMICAL NAME: SILICONE ELASTOMER** 

PHYSICAL FORM: PASTE ODOR: ACETIC ACID

NFPA PROFILE: HEALTH 2 FLAMMABILITY 1 INSTABILITY/REACTIVITY 0

PREPARED BY: AMERICAN CHEMICAL, INC

## SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

CAS NO. <u>% WT</u> <u>INGREDIENT</u>

4253-34-3 <=2.0 METHYLTRIACETOXYSILANE 17689-77-9 <=2.0 ETHYLTRIACETOXYSILANE

THE ABOVE COMPONENTS ARE HAZARDHOUS AS DEFINED IN 29 CFR 1910.1200

## **SECTION 3: HAZARDS IDENTIFICATION**

**ROUTES OF ENTRY: EYE, SKIN, INHALATION, INGESTION** 

#### POTENTIAL HEALTH EFFECTS

**MSDS DATE:** FEB 19, 2015

#### **ACUTE EFFECTS**

**EYES: DIRECT CONTACT MAY CAUSE MODERATE IRRITATION** 

SKIN: MAY CAUSE MODERATE IRRITATION

INGESTION: LOW INGESTION HAZARD IN NORMAL USE

INHALATION: IRRITATES RESPIRATORY PASSAGES VERY SLIGHTLY.

### PROLONGED/CHRONIC EXPOSURE EFFECTS

SKIN: NO KNOWN APPLICABLE INFORMATION

INHALATION: NO KNOWN APPLICABLE INFORMATION

INGESTION: NO KNOW APPLICABLE INFORMATION

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: NO KNOWN APPLICABLE INFORMATION

The above listed potential effects of overexposure are based on actual data, results of studies performed upon similar compositions, component data, and/or expert review of the product. Please refer to Section 11 for the detailed toxicology information.

Page 1 of 5

**SECTION 4: FIRST AID MEASURES** 

EYES: IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL ATTENTION

SKIN: REMOVE FROM SKIN AND WASH THOROUGHLY WITH SOAP AND WATER OR WATERLESS CLEANER. GET MEDICAL ATTENTION IF IRRITATION OR OTHER ILL EFFECTS DEVELOP OR PERSIST.

INGESTION: NO FIRST AID SHOULD BE NEEDED.

INHALATION: NO FIRST AID SHOULD BE NEEDED.

NOTES TO PHYSICIANS OR FIRST AID PROVIDERS: TREAT ACCORDING TO PERSON'S CONDITION AND SPECIFICS OF EXPOSURE.

#### **SECTION 5: FIRE-FIGHTING MEASURES**

FLAMMABLE LIMITS IN AIR: NOT DETERMINED

FLASH POINT: F: > 212° C: >100°

METHOD USED: CLOSED CUP

**AUTOIGNITION TEMPERATURE: NOT DETERMINED** 

EXTINGUISHING MEDIA: ON LARGE FIRES USE DRY CHEMICAL, FOAM, OR WATER SPRAY. ON SMALL FIRES USE CARBON

DIOXIDE (CO2), DRY CHEMICAL OR WATER SPRAY. WATER CAN BE USED TO COOL FIRE EXPOSED

CONTAINERS.

SPECIAL FIRE FIGHTING PROCEDURES: SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING SHOULD BE

WORN IN FIGHTING LARGE FIRES INVOLVING CHEMICALS. DETERMINE THE NEED TO EVACUATE OR ISOLATE THE AREA ACCORDING TO YOUR LOCAL EMERGENCY

**MSDS DATE:** FEB 19, 2015

PLAN. USE WATER SPRAY TO KEEP FIRE EXPOSED CONTAINERS COOL.

UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE

#### HAZARDOUS DECOMPOSITION PRODUCTS

Thermal breakdown of this product during fire or very high heat conditions may evolve the following hazardous decomposition products: Carbon dioxide and traces of incompletely burned carbon compounds. Silicon dioxide. Formaldehyde.

#### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

#### **ACCIDENTAL RELEASE MEASURES:**

OBSERVE ALL PERSONAL PROTECTION EQUIPMENT RECOMMENDATIONS DESCRIBED IN SECTION 5 AND 8. WIPE UP OR SCRAPE UP AND CONTAIN FOR SALVAGE OR DISPOSAL. CLEAN AREA AS APPROPRIATE SINCE SPILLED MATERIALS, EVEN IN SMALL QUANTITIES, MAY PRESENT A SLIP HAZARD. FINAL CLEANING MAY REQUIRE USE OF STEAM, SOLVENTS, OR DETERGENTS. DISPOSE OF SATURATED ABSORBANT OR CLEANING MATERIALS APPROPRIATELY, SINCE SPONTANEOUS HEATING MAY OCCUR. LOCAL, STATE, AND FEDERAL LAWS AND REGUALTIONS MAY APPLY TO RELEASES AND DISPOSAL OF THIS MATERIAL AS WELL AS THOSE MATERIALS AND ITEMS EMPLOYED IN THE CLEANUP OF RELEASES. YOU WILL NEED TO DETERMINE WHICH FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS ARE APPLICABLE. SECTIONS 13 AND 15 OF THIS MSDS PROVIDE INFORMATION REGARDING CERTAIN FEDERAL AND STATE REQUIREMENTS.

SECTION 6 NOTES: SEE SECTION 8 FOR PERSONAL PROTECTIVE EQUIPMENT FOR SPILLS.

#### **SECTION 7: HANDLING AND STORAGE**

HANDLING AND STORAGE: USE WITH ADEQUATE VENTILATION. PRODUCT EVOLVES ACETIC ACID (HOAC) WHEN EXPOSED TO WATER OR HUMID AIR. PROVIDE VENTILATION DURING USE TO CONTROL HOAC WITHIN EXPOSURE GUIDELINES OR USE RESPIRATORY PROTECTION. AVOID EYE CONTACT. AVOID SKIN CONTACT.

OTHER PRECAUTIONS: USE REASONABLE CARE AND STORE AWAY FROM OXIDIZING MATERIALS. KEEP CONTAINERS

CLOSED AND STORE AWAY FROM WATER OR MOISTURE.

OFOTION A EVENOUER CONTROL OFFEDOMAL PROTECTION

**MSDS DATE:** FEB 19, 2015

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

**ENGINEERING CONTROLS** 

**GENERAL VENTILATION: RECOMMENDED** 

RESPIRATORY PROTECTION: NOT NEEDED UNDER AMBIENT CONDITIONS.

EYE PROTECTION: USE PROPER PROTECTION-SAFETY GLASSES AS A MINIMUM. FOR SPILLS, FULL FACE RESPIRATOR.

SKIN PROTECTION: WASH AT MEALTIME AND END OF SHIFT. CONTAMINATED CLOTHING AND SHOES SHOULD BE REMOVED

AS SOON AS PRACTICAL AND THOUROUGHLY CLEANED BEFORE REUSE.

CHEMICAL PROTECTIVE GLOVES RECOMMENDED: BUTYL RUBBER. NEOPRENE RUBBER ®. NITRILE RUBBER.

WORK HYGIENIC PRACTICES: AVOID EYE CONTACT. AVOID SKIN CONTACT. USE REASONABLE CARE.

**EXPOSURE GUIDELINES:** 

CAS NUMBER COMPONENT NAME EXPOSURE LIMITS

4253-34-3 METHYLTRIACETOXYSILANE SEE ACETIC ACID COMMENTS

17689-77-9 ETHYLTRIACETOXYSILANE SEE ACETIC ACID COMMENTS

ACETIC ACID IS FORMED UPON CONTACT WITH WATER OR HUMID AIR. PROVIDE ADEQUATE VENTILATION TO CONTROL EXPOSURES WITHIN GUIDELINES OF OSHA PEL: TWA 10 ppm AND ACHIH TLV: TWA 10 ppm, STEL 15 ppm.

WHEN HEATED TO TEMPERATURES ABOVE 150°C (300°F) IN THE PRESENCE OF AIR, PRODUCT MAY FORM FORMALDEHYDE VAPORS. PHYSICAL AND HEALTH HAZARD INFORMATION IS READILY AVAILABLE FROM HI-TEC INDUSTRIES AND THE MATERIAL SAFETY DATA SHEET.

#### **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

ODOR: VINEGAR-LIKE (ACETIC ACID) SMELL COLOR: CLEAR, WHITE, BLACK, ALUMINUM, BLUE

PHYSICAL STATE: PASTE

pH AS SUPPLIED: NOT DETERMINED

SPECIFIC GRAVITY @25°C: 1.04 BOILING POINT: > 100°C

MELTING POINT/FREEZING POINT: NOT DETERMINED VAPOR PRESSURE (mmHg): NOT DETERMINED VAPOR DENSITY: NOT DETERMINED NOT DETERMINED VISCOSITY: NOT DETERMINED NOT DETERMINED

VOLATILE CONTENT: 29 G/L

The above information is not intended for use in preparing product specifications.

## **SECTION 10: STABILITY AND REACTIVITY**

CHEMICAL STABILITY: STABLE

**INCOMPATIBILITY (MATERIAL TO AVOID):** 

OXIDIZING MATERIAL CAN CAUSE A REACTION. WATER, MOISTURE, OR HUMID AIRE CAN CAUSE HAZARDOUS VAPORS TO FORM AS DESCRIBED IN SECTION 8.

HAZARDOUS POLYMERIZATION: HAZARDOUS POLYMERIZATION WILL NOT OCCUR.

CONDITIONS TO AVOID (POLYMERIZATION): NONE

**SECTION 11: TOXICOLOGICAL INFORMATION** 

TOXICOLOGICAL INFORMATION: NO KNOWN APPLICABLE INFORMATION

SECTION 12: ECOLOGICALINFORMATION

**ENVIRONMENTAL FATE AND DISTRIBUTION:** Complete Information Not Available

**ENVIRONMENTAL EFFECTS**: Complete Information is Not Yet Available

FATE AND EFFECTS IN WASTE WATER TREATMENT PLANTS: Complete Information is Not Yet Available

**Ecotoxicity Classification Criteria** 

Hazard Parameters (LC50 or EC50)	High	Medium	Low
Acute Aquatic Toxicity (mg/L)	<=1	<1and <=100	>100
Acute Terrestrial Toxicity	<=100	>100 and <=2000	>2000

**MSDS DATE:** FEB 19, 2015

This table is adapted from "Environmental Toxicology and Risk Assessment". ASTM STP 1179, p.34, 1993

This table can be used to classify the ecotoxicity of this product when ecotoxicity data is listed above. Please read the other information presented in the section concerning the overall ecological safety of this material.

**SECTION 13: DISPOSAL CONSIDERATIONS** 

RCRA HAZARD CLASS (40 CFR 261)

SECTION 13 NOTES: When a decision is made to discard this material, as received, is it classified as a hazardous waste? NO

Check State and Local laws for additional regulatory requirements regarding disposal.

## **SECTION 14: TRANSPORT INFORMATION**

#### **DOT Road Shipment Information (49 CFR 172.101)**

Not subject to DOT

## Ocean Shipment (IMDG)

Not subject to IMDG code.

## Air Shipment (IATA)

Not subject to IATA regulations

### **SECTION 15: REGULATORY INFORMATION**

#### **U.S. FEDERAL REGULATIONS**

Contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200

TSCA (TOXIC SUBSTANCE CONTROL ACT): All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

Section 304 CERCLA Hazardous Substances (40 CFR 302): None

EPA SARA TITLE III: Section 302 Extremely Hazardous Substances (40 CFR 355): None

#### 311/312 HAZARD CLASS (40 CFR 370):

Acute:: Yes Chronic: No Fire: No Pressure: No Reactive: No

313 REPORTABLE INGREDIENTS: None present or none present in regulated quantities.

### **SECTION 15: REGULATORY INFORMATION**

### **STATE REGULATIONS:**

#### CALIFORNIA

Warning: This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproduction harm. **None Known.** 

**MSDS DATE:** FEB 19, 2015

#### **MASSACHUSETTS**

	CAS Number	Wt%	Component Name		
	7631-86-9	7.0 – 13.0	Silica, amorphous		
NEW JERSEY					
	CAS Number	Wt%	Component Name		
	70131-67-8	70.0 - 90.0	Dimethyl siloxane, hydroxyl-terminated		
	7631-86-9	7.0 – 13.0	Silicon dioxide		
	64742-46-7	<=7.0	Hydrotreated middle petroleum distillates		
	4253-34-3	1.0 – 5.0	Methyltriacetoxysilane		
	17689-77-9	1.0 – 5.0	Ethyltriacetoxysilane		
PENNSYLVANIA					
	CAS Number	Wt%	Component Name		
	70131-67-8	70.0 - 90.0	Dimethyl siloxane, hydroxyl-terminated		

# SECTION 16: OTHER INFORMATION

7631-86-9

64742-46-7

PREPARATION INFORMATION: Prepared by AMERICAN CHEMICAL, INC

7.0 - 13.0

<=7.0

#### DISCLAIMER:

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

Silicon dioxide

Hydrotreated middle petroleum distillates