



HUMIDI-TECH®

Electric-to-Steam Humidifier

- *Adaptable*
- *Reliable*
- *Easy to maintain*
- *Comprehensive control with Vapor-logic®*

Versatility for finished spaces



HUMIDI-TECH HUMIDIFIER

Humidi-tech humidifiers use heat caused by electrical resistance in submerged heating elements to boil fill water into steam. Humidi-tech is compatible with all water types and numerous dispersion options, including matching Space Distribution Units that can be mounted remotely or on top of the Humidi-tech, as shown above.

The Humidi-tech humidifier is a compact, cabinet-style unit compatible with all water types (tap, softened, deionized, reverse osmosis) and numerous dispersion options. Installation is a snap — just attach the frame to a supporting structure and connect electrical and water services.

Available matching Space Distribution Units disperse steam with no visible vapor trail, making Humidi-tech ideal for use in finished spaces.

VERSATILE

- Uses tap, softened, or RO/DI water
- Capacity from 2.7 to 46 kg/h, link up to 16 units for capacity up to 740 kg/h
- Disperses steam through ductwork with dispersion tubes or panels, or directly into a room with a Space Distribution Unit (SDU) mounted remotely or on top of the Humidi-tech

FLEXIBLE

- Control to $\pm 3\%$ RH
- On-off or time-proportioned (TP) control for application control in most environments; solid-state relay (SSR) option for tight control
- Electronically monitored water level ensures safe and reliable operation

EASY TO MAINTAIN

- Removable cover allows easy access to evaporating chamber and electrical connections
- Softened water significantly reduces maintenance requirements
- End-of-season autodrain minimizes microbial growth
- User-adjustable water skimmer skims off floating minerals
- Controller-operated drain and flush removes precipitated minerals from evaporating chamber
- Constant thermal expansion and contraction of heating elements continuously sheds mineral buildup

COMPREHENSIVE CONTROL WITH VAPOR-LOGIC

Vapormist with Vapor-logic sets new standards for control in electric steam humidification:

Interoperability allows communication with building automation systems via Modbus or with optional BACnet or LonTalk protocols.

Safety presets initiate fill and drain cycles and keep the humidifier cool and safe if sensed conditions, though unlikely, could be hazardous.

Web-enabled control allows you to set up, view, and adjust humidifier functions via Ethernet, either directly or remotely through a network.

STATUS	ALARMS	DIAGNOSTICS	SETUP	HELP
System Status				
SPACE RH	SET POINT	OUTPUT		
33%	35%	12.3%		
RUN MODE: Auto				
TANK STATUS: Boiling				
Alarms 0 active alarms View Alarms				
Messages 0 active messages View Messages				
TANK STATUS:				
Run Mode	Auto	CHANGE		
Space RH	35%	CHANGE		
Fill set point	35%	CHANGE		
Input signal	9.3 mA			
Steam output	12.3%			
Steam production	37.4 lbs/hr			
Duct HL switch	Closed			
Tank temperature	144°F			
Tank temp signal	1637 Ohms			
High water probe	Water			
Mid water probe	Water			
Low water probe	Water			
Fill valve	Closed			
Drain valve	Closed			
Airflow switch	Flow			
Interlock switch	Closed			
H2O until drain/flush	9120 lbs			
H2O until service	30400 lbs			
High probe signal	1			
Mid probe signal	1			
Low probe signal	1			

Table 3-1:
Humidi-tech electrical specifications, capacities and weights

HT model	Single-phase 230V		Three-phase 400V		Shipping weight (kg)	Operating weight (kg)
kW	Steam capacity (kg/h)	I max. (A)	Steam capacity (kg/h)	I max. (A)		
2	2.5	8.0	—	—	37	44
4	5.0	16.0	5.4	8.7*	37	44
6	7.5	24.0	8.2	13.0*	41	56
8	10.0	31.9	10.9	17.3*	41	56
10	12.5	39.9	13.6	15.2*	43	64
12	15.0	47.9	16.3	17.3	43	64
14	—	—	19.1	20.2	43	64
16	—	—	21.8	23.1**	43	64
21	—	—	28.6	30.3**	44	70
25	—	—	34.0	36.1**	44	70
30	—	—	40.8	43.3**	47	72
34	—	—	46.3	49.1**	47	72

* For wire sizing, the highest leg draw is shown due to current imbalance.

** No available SDU option for these models.

Notes:

- SDU-I is available for Models HT-2 through HT-10.
- SDU-E is available for all models, except Model HT-2 and Models HT-16 through HT-34.
- Models with the SDU option have additional electronic components in the Humidi-tech cabinet. If adding an SDU, add the following to the Humidi-tech shipping and operating weights:
SDU-E: 5.5 kg
SDU-I: 4.0 kg
- All Humidi-tech humidifiers operate at 50/60 Hz.
- SDUs ship separate from the Humidi-tech.

driSteem Corporation

A subsidiary of Research Products Corporation
An ISO 9001:2000 certified company

European office:

Marc Briers
Grote Hellekensstraat 54 b
B-3520 Zonhoven
Belgium
+321 1823595 (voice)
+321 1817948 (fax)
E-mail: marc.briers@dristeem.com

U.S. Headquarters:

14949 Technology Drive
Eden Prairie, MN 55344
800-328-4447 or 952-949-2415
952-229-3200 (fax)

Continuous product improvement is a policy of driSteem Corporation; therefore, product features and specifications are subject to change without notice.

driSteem, Humidi-tech, Rapid-sorb, STS, Ultra-sorb, and Vapor-logic are registered trademarks of driSteem Corporation and are filed for trademark registration in Canada and the European community.

Product and corporate names used in this document may be trademarks or registered trademarks. They are used for explanation only without intent to infringe.

Ultra-sorb is covered by the following Patents, with additional patents pending: United States Patent numbers 5,126,080; 5,277,849; 5,372,753; 5,376,312; 5,543,090

© 2013 driSteem Corporation



Form No. HT-Product-Brochure-0113

EXPECT QUALITY FROM THE INDUSTRY LEADER

For more than 45 years, driSteem has been leading the industry with creative and reliable humidification solutions. Our focus on quality is evident in the construction of the Humidi-tech humidifier. driSteem leads the industry with a Two-year Limited Warranty and optional extended warranty.

For more information

www.dristeem.com
sales@dristeem.com

For the most recent product information visit our website:

www.dristeem.com

Your driSteem Distributor is: